



Galil 6-I

6.5-Inch, 2-Way Open-Back Rectangular
In-Wall Speakers

| Speakers



The Galil 6-I is a pair of two-way, open-back speakers designed for mounting in the wall. They have an infinite baffle design and aluminum grills

FEATURES

Type - 2-way open-back in-wall speaker with infinite baffle design

Woofer - 6.5" (165mm) polypropylene with rubber surround

Tweeter - 1" (25.4mm) silk

Frequency Response - 50Hz to 20kHz @-15dB, 60Hz to 20kHz @±3dB

Impedance - 8Ω

Sensitivity - 87dB SPL, 1W@1m

Recommended Power - RMS 80W, 220W continuous program

Grill - White baffle with aluminum grills with UV treatment compliance. Locking arms for quick in-wall installation

Package Includes - 2 speakers (1 pair), template and user manual



KRAMER

TECHNICAL SPECIFICATIONS

SPEAKER TYPE:	2-way in-wall speakers
FREQUENCY RESPONSE:	50Hz to 20kHz @-15dB, 60Hz to 20kHz @±3dB
WOOFER:	6.5" (165mm) polypropylene with rubber surround
TWEETER:	1" (25.4mm) silk
IMPEDANCE:	8Ω
SENSITIVITY:	87dB SPL, 1W@1m
MAX. SPL:	Continuous: 109dB, peak: 112dB
POWER HANDLING:	80W RMS, 220W continuous program
CROSSOVER FREQUENCY:	1.8kHz
COVERAGE ANGLE:	107Deg. (if mounted on the ceiling)
DIRECTIVITY FACTOR (Q):	3.4, averaged 1kHz to 10kHz
DIRECTIVITY INDEX (DI):	5.3dB averaged 1kHz to 10kHz
INPUT CONNECTOR:	Terminal block
MATERIALS:	ABS Frame, aluminum grill, safety cord attached to the grill
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	-40° to +70°C (-40° to 158°F)
HUMIDITY:	10% to 90%, RHL non-condensing
WEIGHT PER SINGLE SPEAKER:	1.6kg (3.5lbs) approx
SHIPPING WEIGHT (FOR PAIR):	3.8kg (8.4lbs) approx
INSTALLATION CLEARANCE:	Mounting depth: 7cm (2.76") Cutout dimensions: 18.5cm x 27.3cm (7.28" x 10.75"), W, H
INCLUDED ACCESSORIES:	Cutout template
COLORS:	Available in white
OPTIONS:	Kramer SKIC mounting kit