


# EVOKO LISO

## TECHNICAL SPECIFICATION

### TECHNICAL INFO

- Display
  - 8 inch capacitive touch with anti-fingerprint treatment
- Connectivity
  - Wi-Fi
    - 802.11 a/b/g/n
  - Ethernet
    - RJ-45, 10/100/1000 Mbit
    - PoE & PoE +
      - IEEE 802.3af
  - RFID 13.56 MHz reader
    - ISO/IEC 14443A/B
    - Supports MIFARE 4K/1K card (does not support ISO/IEC 15693 or MIFARE Ultralight C)
- Power
  - Power over Ethernet (PoE), or
  - 12V AC/DC power adapter (accessory)
- Sensors
  - Proximity sensor
  - Ambient light sensor
- Mounting
  - Mounting options for both standard and glass walls
  - 5-way cable exit option for easy and neat installation
- Other
  - 3-way indirect light aura to make room status visible already from a distance
  - Open API for third party integration
  - Communication via real-time two-way connection
  - Remote management with multi-site support
  - Real-time monitoring & statistics
- Server
  - Recommended Specifications: Dual Core CPU-4GB-30GB



### COMPATIBLE PLATFORMS

- Microsoft Office 365
- Microsoft Exchange 2016
- Microsoft Exchange 2013
- Microsoft Exchange 2010 SP3
- Google G Suite
- IBM/Lotus Domino Smartcloud
- IBM/Lotus Domino 8.5.3 – 9.x
- Evoko Booking (stand-alone version)

### SIZE AND WEIGHT

- Size: 200 x 200 x 25 mm (7.9 x 7.9 x 1.0 inch)
- Weight: 1.3 kg (2.9 lbs)

### USER INTERFACE LANGUAGES

- Arabic
- Catalan
- Chinese, Simplified
- Chinese, Traditional
- Czech
- Danish
- Dutch
- English
- Estonian
- Finnish
- French
- Galician
- German
- Italian
- Icelandic
- Japanese
- Korean
- Latvian
- Lithuanian
- Norwegian
- Polish
- Portuguese
- Russian
- Spanish
- Swedish
- Thai

### PRICING MODEL & BOX CONTENTS

Our pricing model is based on the same simplicity as our products; it is a one-time cost per unit and that is it. There are no licensing costs or subscription fees and all required hardware, software, support and warranty are included. The one-time cost includes:

- Evoko Liso unit (hardware with Liso application)
- Mounting kits for both standard and glass walls
- Evoko Home application (used for configuration, synchronization and administration)
- Future software upgrades for the Evoko Liso unit and Evoko Home
- Power Supply (if needed, typically installed with PoE)
- 2-year warranty (up to 3 more years can be purchased separately)
- Product support via phone/email/web-tickets for as long as the Liso units are used

### ARTICLE NUMBER

- ERM2001