

# HDMI KVM Extender Set with USB 2.0 Extension

## EX-80-KVM



## Quickstart Guide

⚠ WyreStorm recommends reading through this document in its entirety to become familiar with the product's features prior to starting the installation process.

HDMI HDCP POC


### ⚠ IMPORTANT! Installation Requirements

- Read through the [Wiring and Connections](#) section for important wiring guidelines before creating or choosing premade cables.
- Visit the product page to download the latest firmware, document version, additional documentation, and configuration tools.

### In the Box

- 1x EX-80-KVM Transmitter
- 1x EX-80-KVM Receiver
- 1x 12V DC 2A Power Supply (US/UK/EU/AU)
- 1x USB Type B to Type A Cable
- 4x Mounting Brackets

### Basic Wiring Diagram



### Warranty Information

WyreStorm Technologies ProAV Corporation warrants that its products to be free from defects in material and workmanship under normal use for a period of five (5) years from the date of purchase. Refer to the Product Warranty page on [wyrestorm.com](http://wyrestorm.com) for more details on our limited product warranty.




## Wiring and Connections

WyreStorm recommends that all wiring for the installation is run and terminated prior to making connections to the switcher. Read through this section in its entirety before running or terminating any wires to ensure proper operation and to avoid damaging the equipment.

### **IMPORTANT! Wiring Guidelines**

- The use of patch panels, wall plates, cable extenders, kinks in cables, and electrical or environmental interference will have an adverse effect on signal transmission which may limit performance. Steps should be taken to minimize or remove these factors completely during installation for best results.
- WyreStorm recommends the use of shielded category cable to minimize signal noise and interference.
- WyreStorm recommends using pre-terminated HDMI cables due to the complexity of these connector types. Using pre-terminated cables will ensure that these connections are accurate and will not interfere with the performance of the product.

### Cat6 Cable Performance Guide



WyreStorm recommends the use of shielded cable to minimize signal noise and interference

## Troubleshooting

### No or Poor Quality Picture (snow or noisy image)

- Verify that power is being supplied to the transmitter and receiving device.
- Verify that all HDMI and UTP connections are not loose and are functioning properly.
- Verify that the UTP cable is properly terminated following EIA568B standard.
- Verify that the output resolution of the source and display is supported by this extender.

### Failed USB Connection or Slow Transmission rate

- Ensure the category cable length is within the range of requirement, USB HID device is within 80m/260ft, USB storage device is within 60m/200ft.

### **Troubleshooting Tips**

- WyreStorm recommends using a cable tester or connecting the cable to other devices to verify functionality.