

SP200T, SP203

Internal Sounders

VANDERBILT



Key Features include:

- Range of internal electronic sounders
- Variable output
- Tone selection
- Low current consumption
- High Output
- Encapsulated electronics

SP200T, SP203

Internal Sounders

VANDERBILT

	SP200T	SP203
Supply voltage	9...14.5 V DC	9...14 V DC
Current consumption	140 mA	20...140 mA
Output at 1m	110 dB	70...110 dB
Tones	1	4
Dimensions (W x D x H) mm	135 x 35 x 100	135 x 35 x 100
IP Rating	IP31	IP31
Tamper – Removal & Cover	Included	Included
Construction	ABS White	ABS White
Operating temperature	-10...+40°C	-10...+40°C
Approvals	-	SBSC, DNV, ANPI

■ Ordering Information

Type	Art No.	Description	Weight
SP200T	N54539-Z155-A100	Internal sounder, with tamper	0.23 kg
SP203	N54539-Z147-A100	Internal sounder, with tamper	0.23 kg

Issued by
Vanderbilt
Clonshaugh Business and
Technology Park
Clonshaugh
Dublin 17
Ireland
www.vanderbiltindustries.com

Data and design subject to change without notice.
Supply subject to availability.

VANDERBILT