



PT-SW-U324

2x4 USB3 Switch - 5Gbps



FRONT



BACK

Features

- ▶ Dual auto-switching USB 3.2 Gen1 Host ports (USB-B) with data transfer rates of up to 5Gbps
- ▶ Quad USB 3.2 Gen1 device ports - 2x USB-C and 2x USB-A with MTT support for improved data handling
- ▶ Over current protection with 7.5W power per USB-C device port and 5W per USB-A device port
- ▶ Mountable ProAV housing and locking PSU and RS232 / panel button control
- ▶ USB device ports compliant with USB 3.2 Gen1, USB 2.0 and USB 1.1

Technical Data
PT-SW-U324

Input / Output	
Input	2x USB HOST (USB 3.2 Gen1 Type-B)
Output	2x DEVICE (USB-C) - 2 hub tiers, 2x DEVICE (USB-A) - 1 hub tier
Control	1x RS232 (3-pin Phoenix)
Technical Data	
USB Protocol	USB 3.2 Gen1
Transfer Rate	5Gbps
USB-A device power	5V / 1A
USB-A device tier level	1 additional hub tier
USB-C device power	5V / 1.5A
USB-C device tier level	2 additional hub tiers
Full Speed Transaction handling	MTT support
USB powering	Always-on or Follow Host
Optimal passive transmission distance	1.5m over USB cable
ESD Protection	IEC 61000-4-2: ±8kV (Air-gap discharge), ±4kV (Contact discharge)
General	
Product Dimensions	125 x 80 x 30mm
Product Weight	317g
Housing Material	Steel
Colour	Black
Operation Temperature	0 ~ 40°C
Storage Temperature	-20 ~ 60°C
Relative Humidity	10% ~ 90%
Power Supply	DC 12V / 3A
Power Consumption	Max. 30W

Set includes

Art.-No.	EAN
PT-SW-U324	4251364745861

Contact

PureLink GmbH
Von-Liebig-Str. 10
48432 Rheine | Germany

 +49 5971 800 299-0
 +49 5971 800 299-99
 info@purelink.de



We regularly expand our product range. We will be happy to provide information on updates in this regard upon request.
All information is subject to confirmation and non-binding. Technical changes, printing errors and mistakes excepted.
The illustrations used in this document may differ from the delivered product.