

EasyIP 5 ePTZ CAMERA

AV-over-IP ePTZ CAMERA WITH AUTOFRAMING TECHNOLOGY

999-30150-000 (worldwide)

OVERVIEW

The EasyIP 5 ePTZ camera has a wide 100° field of view, making it perfect for an audience overview shot in a larger room or for getting everyone in the frame in small collaboration rooms and huddle spaces. EasyIP 5 eliminates the need for costly USB extenders by sending 1080p resolution video feeds to EasyIP endpoints over category cables.

Use EasyIP 5 with endpoints like the EasyIP Decoder for a USB output that connects you with your favorite conferencing software like Microsoft Teams, Google Meet and Zoom. Integrate the EasyIP 5 with existing video and audio systems and gain useful features like picture-in-picture and graphic overlays using the EasyIP Mixer.

Offering superior flexibility for various environments, installers can select one of three primary settings for how sensitive you want the camera's auto-framing to be. Conservative Conference is designed for low-motion environments, Responsive Conference is the perfect option when you have teams that utilize the whole room, and Default Conference is the sweet spot where most teams are happy with the system performance.

An included Wall Mount Bracket allows the camera to tilt up and down to ensure proper framing of the conference table or room. Additional ceiling and on-display mounts are available separately.

FEATURES

- 5x zoom with 100° horizontal field of view
- One EasyIP (PoE+) network video output, plug-and-play with EasyIP endpoints
- Customizable auto-framing for a variety of environments



EasyIP 5 ePTZ CAMERA

AV-over-IP ePTZ CAMERA WITH AUTOFRAMING TECHNOLOGY

TECHNICAL SPECIFICATIONS

		999-301500-000
VIDEO OUTPUT	Outputs/protocols	EasyIP
	Aspect ratio	16:9, 4:3 and 3:2
	Resolutions/frame rates	Up to 1080p/30
	Image device	1/18" -Type CMOS sensor
	Pixels	8 million
	Lens and Horizontal FOV	5x digital zoom, 100° (Wide End) 24° (Tele End)
	Min. working distance	250 mm
	Min. illumination	100+ lux recommended
	Backlight compensation	On/off
	Focusing system	Auto Focus, Fixed
	Gain	Auto/Manual (0 to 33 dB)
	White balance	Auton, ATW, Indoor, Outdoor, One-push, Manual
	S/N ratio	More than 50 dB
	Power	PoE
	Remote management	IR Remote, web interface, Telnet; compatible with Vaddio Device Controller
	Presets	16+ Custom Home
	Invertible	Yes
Manual Tilt Range	-15°, +20°	
Warranty	3 years with 1 year Advance Replacement	
HARDWARE	Weight	1.95 lbs (0.88 kg)
	Height	6.89 in. (17.5 cm)
	Width	4.72 in. (12 cm)
	Depth	2.17 in. (5.5 cm)
	Operating/storage temperature	32° F to 104° F (0° C to +40° C)
	Operating/storage humidity (relative)	20% to 80% RH, non-condensing

WHAT'S IN THE BOX

- EasyIP 5 ePTZ Camera
- Wall mount with tilting feature and mounting hardware
- Vaddio IR Remote Master
- 3.3 ft (1m) cat-5e snagless cable
- Quick-start card



LEGRAND | AV COMMERCIAL BRANDS
C2G | Chief | Da-Lite | Luxul | Middle Atlantic | Vaddio | Wiremold

THE ART OF EASY | legrandav.com

USA 800.572.2011 avvaddio.support@legrand.com

EMEA +31 495 580 840 av.emea.sales@legrand.com APAC +852 2145 4099 avasia.sales@legrand.com

©2024 Legrand AV Inc. 231010 Rev A 12/23 Vaddio is a registered trademark of Legrand AV Inc. All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All patents are protected under existing designations. Other patents pending.