

SUPERIOR Product line

Superior KeyPad Outdoor Fibra

Wired outdoor and indoor keypad supporting authentication via Pass, Tag, smartphones, and codes

This is the device of the Superior product line. Only accredited Ajax Systems partners can sell, install, and administer Superior products.



Contactless authorization

- Pass cards and Tag key fobs supporting DESFire® technology
- Smartphones with Bluetooth via BLE technology
- Remote configuration of access control devices
- Protection against authentication via unauthorized access devices

***- Management with codes

2

DESFire

₿

- Four types of codes: for registered users, for unregistered users, a keypad code, and an RRU code
- Keypad locking when someone tries to guess the code
- Duress code: if a user is forced to disarm the facility
- Remote management: codes can be created, changed, or removed in Ajax apps

Additional features

Big mechanical buttons with a resilient press mechanism for easy and fast access, even in gloves and mittens

Automation devices control along with security mode change

A built-in 60 dB buzzer to inform about alarms, security mode changing, Chime, etc.

Authorization confirmation: arming/disarming using access control devices requires confirmation with a code

Bypass mode: initiated at delay when entering/leaving in case of changing security mode to confirm arming/ disarming via the main keypad





Sabotage resistance

- Tamper alarm: the enclosure is hardwired with two tamper buttons
- IK08 enclosure impact protection
- Device authentication to prevent spoofing
- Protection from short circuits on the Fibra line
- Holding screw to secure the device on SmartBracket
- Panic button in case of emergencies

communication technology

- Up to 2,000 m (6,550 ft) of wired communication with a hub or module that extends the Fibra line¹
- Data is encrypted throughout the transmission process
- Regular polling to display current device states
- One Fibra line for different types of devices
- Energy consumption of up to 0.6 W

Quick installation and setup

- IP66 enclosure for outdoor and indoor use
- Installation without disassembling the enclosure
- Pairing with a hub via the line scanning feature or QR code
- On-site or remote configuration and testing

Compliance	Communication with a control panel	Features	Installation
In progress: EN 50131 (Grade 3) PD 6662:2017 SSF	Fibra communication technology	Contactless access Pass cards and Tag key fobs (up to 50 devices)	Operating temperature range from -25 °C to +60 °C from -13 °F to 140 °F
	Wired connection U/UTP cat 5 4x2x0 51 cable	Support for BLE	Operating humidity

Compatibility

Hub Hybrid (2G) Hub Hybrid (4G) with a copper conductor

4×0.22 signal cable with a copper conductor

Communication range up to 2,000 m up to 6,550 ft With U/UTP cat.5 4×2×0.51 cable

Polling interval 12–300 s Adjusted by a PRO or user with admin rights in Ajax apps (up to 50 smartphones)

Access codes up to 50 personal codes for registered users

up to 50 codes for unregistered users

1 keypad code

Duress code up to 50 personal duress codes

1 keypad duress code

Panic button

up to 80%

Protection class IP66

Impact protection IK08 (in progress)

Power supply

Enclosure

Complete set

Fibra line	Color	Superior KeyPad Outdoor Fibra	
7-30 V=, up to 0.6 W	white, graphite, black	SmartBracket mounting panel	
		Installation kit	
	Dimensions	Quick start guide	
	137 × 45 × 27 mm		
	5.39" × 1.77" × 1.07"		
	Weight		
	160 g		
	5.6 oz		
	Tamper alarm		

¹ When using a U/UTP cat.5 4×2×0.51 cable.



For detailed information, scan the QR code or follow the link:

ajax.systems/support/devices/superior-keypad-outdoor-fibra/



@AjaxSystemsSupport_Bot

